

BRAINERD, MN
Chapter 515 ZONING

515-2-9 Traditional Neighborhood 2 (TN-2)

- A. **Purpose of Traditional Neighborhood 2 Zoning District.** The TN-2 Zoning District is intended to provide for compact, pedestrian-oriented mix of residential and neighborhood-serving commercial uses. This District reinforces the existing pattern of small, connected lots, blocks and street and supports development and redevelopment consistent with this pattern.
- B. **Permitted Uses.** See Appendix A: Table of Uses.
- C. **TN-2 Zoning District Dimensional Standards.** Table 515-2-9.1 identifies the Dimensional Standards for Principal and Accessory Structures.

Table 515-2-9.1. TN-2 Dimensional Standards – Density, Lot Size, Coverage and Height Standards

Lot Dimensions		
A	Lot Size (minimum) Density (range)	4,000 SF 9 – 20 DU/AC (20+ DU/AC requires CUP)
B	Buildable Area Floor Area Ratio (FAR) for commercial use	Outside of all setbacks 0.5
C	Lot Frontage on All Roads (minimum)	45'
Principal Building & Attached Accessory Building Standards		
D	Front Yard Setback (minimum)	0' - 20' if Commercial is Principal Use, 5' – 20' if Residential is Principal Use
E	Side Yard Setback (minimum)	5'/10' corner
F	Rear Yard Setback (minimum)	10'
	Accessory Building SF, attached	Counts towards Total Allowable SF
	Accessory Building Number, attached	Does not count towards Permitted Number
Accessory Building Standards		
G	Location, detached	behind Principal Building
H	Side Yard Setback, detached (minimum)	5'/10'
I	Rear Yard Setback, detached (minimum)	5'
	Total Allowable Accessory Building SF	750 SF or 10%, whichever is greater
	Total Number of Permitted Accessory Buildings	2
	▪ Exception if no Attached Accessory Building is present, total Number Permitted	3
	Accessory Dwelling Unit (ADU), attached or detached	Permitted on Corner lot, by CUP on interior lot
	▪ Size of ADU, attached or detached (maximum)	650 SF
Coverage and Height Standards		
	Impervious Surface Coverage (maximum)	75%
	Principal structure height (maximum) See Section 515-4-3	35'
	Accessory structure height	Up to 35' but may not exceed height of principal structure
Other Standards		
J	Driveway	If front loaded, Width at ROW maximum is 18'
K	Alley	If present, access and garage/parking is required
L	Garage	If front loaded, must be setback behind façade of principal structure a minimum of 5'
	Sidewalk/Trail Standards	See Subdivision Ordinance Chapter 500

BRAINERD, MN
Chapter 515 ZONING

Figure 515-2-9.1. TN-2 Density and Lot Dimensional Standards Diagram

